

DVG320



Overview

The ballasts of DVG320 series are suitable for uv lamps with lamp current from 120W to 300W.

Electronic ballasts (lamp drivers) offer considerable advantages over conventional devices: they provide quiet, flicker-free light, ignite the lamps gently, increase the life of the tubes while saving energy, and increase the radiation output of the lamps with the same energy input.

The digital ballasts from SES GmbH are microprocessor-controlled and can therefore be optimally adjusted to any lamp. They are available for low-pressure and amalgam lamps and are used especially in the areas of sunbeds, air and water disinfection, UV curing, ozone formation, etc.



Mains
185-253VAC
50/60Hz

Power
120W-300W

I-Lamp
0,8-3,0A

Temp
ta: 5-45°C
tc max: 50°C

IP20

CE

Functionality

- Preheat current and time adjustable by software
- Lamp current adjustable by Software
- Lamp monitoring (current, voltage, cable break)
- Status indication via LED, Error output (relay)
- RS version with RS485 interface

Available Types

- DVG320 Pmax 320W / I-Lamp 0,8-3,0A
 - DVG320-RS Pmax 320W / I-Lamp 0,8-3,0A
- other lamp currents available

DVG320 is a replacement for DVG260. It is fully compatible to DVG260 (excl. new connectors).

Technical Data

| Type | Data |
|---|---|
| Lamp output power | 120W-300W max. |
| Mains voltage | 230 VAC +/-10% |
| Mains Frequency | 50/60 Hz |
| Mains connection | L, N, Protection Ground |
| UV lamp operating voltage | 40V - 160 V (depending on lamp type) |
| UV lamp operating current | ~ 0,8A - 3,0A |
| Ignition voltage | ~ 0,6kV - 1,5kV |
| Duty frequency | ~ 30 kHz / ~ 120kHz |
| Power loss | 2% - max 10 % of total lamp power |
| Powerfactor | >=0,96 |
| Max. distance to lamp | 5m (min 0.5mm²) |
| Status indication | LED and Status relay |
| Ambient temperature, storage / humidity | -5 to +70° C / max. 80%, not condensing |
| Ambient temperature, operating | 5 to 45° C (higher temperature available) |
| Dimension (LxBxH) | Approx. 248 x 90 x 52 mm |
| Weight | ~ 0,4 kg |
| Protection | IP20 |
| Cooling | Air cooling external needed |
| Mounting position | Vertical, mains connector on top |
| Options (Dimming, RS485) | Dimming input 1-10VDC, RS485 (Modbus RTU) |

According to the EMC specifications: EN 61000-6-2, EN 61000-6-4, EN 55011, EN 61000-4-2K-6, EN 61000-4-1161000-6-4, EN 55011, EN 61000-4-2K-6, EN 61000-4-11