

DVG2x320-RS

Overview

The ballasts DVG2x320 series are suitable for 2 uv lamps with lamp power from 100W to 320W.

Electronic ballasts (lamp drivers) offer considerable advantages over conventional devices: they provide quiet, flicker-free light, ignite the lamps gently, increase the life of the tubes while saving energy, and increase the radiation output of the lamps with the same energy input.

The digital ballasts from SES GmbH are microprocessor-controlled and can therefore be optimally adjusted to any lamp. They are available for low-pressure and amalgam lamps and are used especially in the areas of sunbeds, air and water disinfection, UV curing, ozone formation, etc.



Mains
185-253VAC
50/60Hz

Power
2x
100W-320W

I-Lamp
2x
1,0-3,0A

Temp
ta: 5-45°C
tc max: 50°C

IP20

CE

Functionality

- Preheat current and time adjustable by software
- Lamp current adjustable by Software
- Lamp monitoring (current, voltage, cable break)
- Status indication via LED, - Error output (relay)
- DVG2x320-RS with RS485 Interface

Available Types

- DVG2x320 Pmax 320W / I-Lamp 1.0-3,0A
- DVG2x320-RS Pmax 320W / I-Lamp 1.0-3,0A
- other lamp currents available

Technical Data

Type	Data
Lamp output power	100W-320W max.
Mains voltage	230 VAC +/-10%
Mains Frequency	50/60 Hz
Mains connection	L, N, Protection Ground
UV lamp operating voltage	70V - 160 V (depending on lamp type)
UV lamp operating current	~ 1,0A - 3,0A
Ignition voltage	~ 0,6kV - 1,5kV
Duty frequency	~ 30 kHz / ~ 120kHz
Power loss	2% - max 10 % of total lamp power
Powerfactor	>=0,96
Max. distance to lamp	5m (min 0.5mm ²)
Status indication	LED and Status relay
Ambient temperature, storage / humidity	-5 to +70° C / max. 80%, not condensing
Ambient temperature, operating	5 to 45° C (higher temperature available)
Dimension (LxBxH)	Approx. 248 x 180 x 58 mm
Weight	~ 0,5 kg
Protection	IP20
Cooling	Air cooling external needed
Mounting position	Vertical, mains connector on top
Dimming with RS485 interface	Interface RS485, Modbus RTU, different protocols available

According to the EMC specifications: EN 61000-6-2, EN 61000-6-4, EN 55011, EN 61000-4-2K-6, EN 61000-4-1161000-6-4, EN 55011, EN 61000-4-2K-6, EN 61000-4-11